



PART# 901050MR

**2000-2020 GM SUV 2WD/4WD
2000-2020 CADILLAC ESCALADE
MODELS W/ MAGNE/AUTO-RIDE**

5" REAR LIFT KIT



3 HOUR INSTALL TIME



**Recommended Tire size
35x12.50**

NOTE: This kit requires drilling into the bump stop striker plates and the side of the factory trac bar bracket

Components	Hardware	Hardware Pack #
(2) 1650 COIL SPACER	(2) M14-2.0 X 100 HEX CAP SCREW	9010H-RTB
(1) 9010RTB TRAC BAR BRACKET	(2) M14-2.0 NYLOCK NUT	
(2) 9499RSB SWAY BAR END LINK	(4) M14 FLAT WASHER	
(2) 9010RBS BUMP STOP EXTENSION	(2) 7/16-14 X 1 1/4" HEX CAP SCREW	
(1) SEP-541050-D SHOCK EXTENDER	(2) 7/16-14 NYLOCK NUT	
(1) SEP-541050-P SHOCK EXTENDER	(4) 7/16" FLAT WASHER	9010H-RSB
(1) 9010RB-1 BRAKE LINE BRACKET	(2) M12-1.75 X 65 HEX CAP SCREW	
(1) 9010ABS-1D ABS LINE BRACKET	(2) M12-1.75 NYLOCK NUT	
(1) 9010ABS-1P ABS LINE BRACKET	(4) M12 FLAT WASHER	9010H-SEMR
(1) 9010RE-1 E-BRAKE BRACKET	(6) 1/2-13 X 1 1/2" HEX CAP SCREW	
(2) 9010MR-5 REAR SENSOR BRACKET	(4) 1/2-13 JAM NUT	
	(2) 1/2-13 NYLOCK NUT	
	(4) 1/2" SPLIT LOCK WASHER	9010H-RBS
	(8) 1/2" FLAT WASHER	
	(2) 7/16-14 NYLOCK NUT	9010H-BL
	(2) 7/16" FLAT WASHER	
	(2) M8-1.25 X 20 HEX CAP SCREW	
	(2) M8-1.25 NYLOCK NUT	9010H-SB
	(4) M8 FLAT WASHER	
	(2) M6-1.0 X 16 HEX CAP SCREW	
	(2) M6-1.0 X 16 HEX CAP SCREW	
	(4) M6 FLAT WASHER	

Please double check the parts list before beginning installation to ensure all parts are present. If there is something missing, please contact Maxtrac Suspension (714) 630-0363. Please have the boxes present if parts are missing or damaged

PRIOR TO INSTALLATION:

- 1. Factory service manual is recommended to have on hand.**
- 2. Secure and properly block vehicle prior to beginning installation.**
- 3. Always wear safety glasses when using power tools or working under the vehicle**
- 4 Modification to any part will void the warranty associated with that product**


AFTER REMOVING PARTS FROM VEHICLE, SAVE HARDWARE FOR REINSTALLATION EDITED 10/21/2025

4522 E Eisenhower Cir Anaheim, CA 92807 (844) 535-1668 Email: Techsupport@Maxtracsuspension.com

MAXTRACSUSPENSION.COM



Step 1 Jack up the rear of the truck and support under the frame rails with jack stands. Keep an adjustable jack under the diff for height adjustment.




Step 2 Separate the ABS guide clip, on each side, from the frame to allow for more slack during the install.




Step 3 Unclip the ABS line guide clips from the back side of the upper control arm mounts on both sides.



Step 4 First, apply pressure to the diff with the adjustable jack. Next, unbolt both lower shock bolts at the axle and remove the bolts.



Step 5 Unbolt both sway bar end links at both ends and remove.



Step 6 Unbolt the brakeline bracket from on top of the diff to allow for more slack when installing the coil spacers.



Step 7 Locate the E-brake cable guide brackets on the frame in the passenger side wheel well and at the driver's side lower control arm mount on the axle. Unbolt both and completely remove the pass side bracket from E-brake cable.



Step 8 Lower down the axle and remove both coil springs. **NOTE: MAKE SURE TO SAVE THE RUBBER ISOLATORS FOR RE-INSTALLATION.**



Step 9 Unbolt the trac bar from the mount on the frame and separate.



Step 10 Make sure the adjustable jack under the diff has a provision to keep the diff from rotating, then unbolt both lower link arms from the axle, loosen the bolts at the frame, and allow them to both drop down, away from the axle. **NOTE: IF THE PINION IS NOT SUPPORTED, THE DIFF WILL WANT TO ROTATE DOWN.**



Step 11 Locate the bump stop striker pads on the axle, then measure and mark an "X" 2 1/8" straight forward from the existing hole in the plate. Next, drill a 1/2" hole through your mark. **NOTE: CHECK THE FACTORY HOLE FOR WELD SLAG. IT MAY NEED TO BE CLEANED OUT TO ACCEPT A BOLT.**




Step 12 Install the provided bump stop extension and secure it by installing the provided 7/16" nut and washer on the most forward bolt and tighten. The further back bolt is just a guide. **NOTE: THIS AREA IS ONLY ACCESSABLE WHILE THE LOWER CONTROL ARM IS REMOVED FROM THE BRACKET ON THE AXLE.**



Step 13 Locate the coil spacers and loosely install them along with the factory coils and isolators. Once both are in place, jack up the axle to apply pressure to the coils and assure that they are properly seated.



Step 14 Loosely re-attach the lower control arm to the axle and only snug up the nuts. **NOTE: THESE BOLTS WILL GET FULLY TIGHTENED WHEN THE TRUCK IS BACK ON THE GROUND AT RIDE HEIGHT.**



Step 15 Loosely install the provided shock extenders, using the provided 1/2" bolts, lock washers and jam nuts through the original shock mounting holes, from the outside inward. You will then install the provided 1/2" bolts through the bottom hole and attach using the provided nylock nuts.



Step 16 First snug up the bottom bolt to square up the bracket, then fully tighten the two side bolts and torque to 50 ft/lbs. Next, go back to the bottom bolts and torque to 50 ft/lbs.



Step 17 Loosely install the provided trac bar bracket onto the factory trac bar bracket on the passenger side frame using the provided 14mm bolt and zinc plated crush tube. The rearward facing ear of the provided bracket will install "inside" the factory bracket and the forward facing ear will install on the "outside" of the factory bracket.



Step 18 Using a scribe, trace the upper, side hole of the trac bar bracket, then remove the bracket and drill a 1/2" hole through your circle.



Step 19 Re-install the bracket using the provided zinc plated crush tube and 14mm hardware. Next, install the provided 7/16" bolts, nuts, and washers through the two side holes. You will also be attaching the provided pass side ABS line bracket to the upper bolt with the "D" shaped hole facing upward, then tighten all 3 bolts. Torque the M14 bolt to 100 ft/lbs and the 7/16" bolts to 45 ft/lbs.



Step 20 Loosely attach the trac bar to the new drop down bracket using the factory bolt and nut. **NOTE: DO NOT FULLY TIGHTEN THIS BOLT UNTIL THE TRUCK IS BACK ON THE GROUND AT RIDE HEIGHT.**



Step 21 Slide the E-brake guide bracket onto the E-brake cable near the trac bar bracket on the passenger side and then attach this bracket to the small hole on the back of the trac bar bracket using the provided 8mm bolt nut and washers. **NOTE: DO NOT FULLY TIGHTEN THIS BRACKET. ONLY SNUG IT UP AS IT WILL NEED TO PIVOT AS THE SUSPENSION CYCLES.**



Step 22 Remove the "O" ring that is on the factory mounting bolt for the brake line bracket at the top of the diff. Next, attach the provided brake line bracket to the top of the diff using this bolt and tighten.



Step 23 Gently bend the hard brakelines until the factory mounting bracket is vertical and the soft brakelines are pointed straight up. Next, attach the factory brakeline bracket to the provided brakeline bracket using the provided 8mm bolt, nut, and washers.



Step 24 Install the new, longer sway bar end links using the factory bolt at the frame and the provided 12mm bolt at the sway bar, then tighten.



Step 25 Pop off the sensor linkage from the ball mount on the rear, upper control arm using a pry or wedge. Next, unbolt the factory ball mount and attach the provided extension brackets in its place using the provided M6 bolt and washer. The bracket will interlock under the attachment bolt of the bracket to the arm and align outwar of this bracket.



Step 26 Attach the factory ball mount to the upper hole in the provided bracket using the provided M6 washer and lock nut. The ball needs to face outward in the wheel well.

Step 27 Re-install the wheels and tires then lower the truck to the ground. Jump on the rear bumper a few times to settle the suspension and then tighten all of the control arm/ trac bar bolts that were left loose to factory specs. Next, re-attach the E-brake cable guide bracket to the driver's side lower control arm and tighten.

AFTER MODIFYING YOUR SUSPENSION

HAVE THE VEHICLE'S ALIGNMENT CHECKED

PROPERLY ADJUST YOUR HEAD LIGHTS FOR THE NEW STANCE OF THE SUSPENSION

RE-TORQUE ALL BOLTS AFTER 500 MILES





MaxTrac
s u s p e n s i o n

RIDE HEIGHT SHEET

*THIS SHEET MUST BE FILLED OUT PRIOR TO CALLING WITH ANY DISCREPENCIES

YEAR _____ MAKE _____ MODEL _____

4WD / 2WD / AWD

MEASUREMENTS

*MOST ACCURATE MEASUREMENT IS FROM THE BOTTOM OF THE RIM, STRAIGHT UP TO THE BOTTOM OF THE FENDER

*TRUE HEIGHT WONT BE ACCURATE UNTIL VEHICAL IS ALIGNED

*THE VEHICLE'S CASTER WILL BE INCREASED OR DECREASED IF ONLY THE FRONT OF THE VEHICLE IS MODIFIED

	BEFORE	AFTER	DIFFERENCE
DRIVER FRONT	_____	_____	_____
DRIVER REAR	_____	_____	_____
PASSENGER FRONT	_____	_____	_____
PASSENGER REAR	_____	_____	_____

LIMITED LIFETIME WARRANTY

Max Trac Suspension makes no warranty, expressed or implied, as to the merchantability, fitness for purpose, description, quality, productiveness, accuracy or any other matter with respect to every product, all such warranties being hereby specifically and expressly disclaimed by Max Trac. Max Trac may offer technical advice or assistance with regard to the products based on laboratory and/or field experience and customer understands and agrees that such advice represents only good faith opinions and does not constitute a warranty or guarantee. The sole and express warranty provided by Max Trac is to warrant that the products sold as listed comply with Max Trac's specification at the date and time of manufacture. Max Trac makes no warranty that such products shall meet such specification at any time after installation of products. Use of such product is specifically not warranted, and Max Trac specifically excludes from this express warranty parts subject to normal wear and tear after one year, finish after one year, damage resulting from failure to follow recommendations in installation manuals, competition or off-road use, and damages caused by aftermarket products. Max Trac's liability and customer's exclusive remedy for any breach of this limited express warranty is limited to repair, replacement, or refund at Max Trac's option and in Max Trac's sole discretion. There are no warranties which extend beyond the description on the face hereof.

Our limited lifetime warranty excludes the following items: bushings, bump stops, ball joints, tie rod ends, rod end/heim joints, and shock absorbers. These parts are subject to immediate wear and tear and are not considered defective when worn. They are warranted for twelve (12) months from the date of purchase only for defects in workmanship.

This Max Trac warranty is void if (1) the vehicle is not aligned after kit installation, (2) proper maintenance is not routinely performed, (3) the Max Trac products are misused or abused in any way in either installation or service, or (4) the products are used in a way that violates federal, state, or local law or regulation in any respect. Max Trac is not responsible for vehicle compatibility with other aftermarket products. Warranty coverage does not include consumer opinions regarding ride comfort, fitment and design after product installation.

Max Trac reserves the right to change, modify or cancel this warranty without prior notice.

WARRANTY RETURN

Contact Maxtrac by sending an email with a copy of the original purchase receipt, along with photographs clearly illustrating the failure mode.

1. Upon validating the information provided, Maxtrac will issue a Return Manufacturer Authorization number (RMA#).
2. Return your product to Max Trac Suspension at your expense in order to execute a claim under this warranty.
3. Include the RMA# on the outside of the box. Any returns without the RMA# will be refused.

NON-WARRANTY RETURN & CREDIT POLICY

Your item must be in its original unused and resalable condition to be returned, unless there is a manufacturing defect. You must return the item within 30 days of your purchase. Otherwise, there will be an additional restocking fee.

1. Please contact Max Trac Suspension at (844) 535-1668 to obtain a Return Manufacturer Authorization Number (RMA#).
2. Return your product to Max Trac Suspension at your expense.
3. Include the RMA# on the outside of the box. Any returns without the RMA# will be refused.

Return Exceptions

Merchandise that has been installed, used, or altered may be subject to no credit.

Restocking Fee

All items are subject to a restocking fee based on the condition of the packaging and product.

Max Trac Suspension does not credit shipping and handling. Credit minus applicable restocking fee will be determined and issued within 10 business days of product receipt.

All returns will be credited to your Maxtrac account.



INSTALLATION WARNINGS

READ INSTRUCTIONS AND WARNINGS COMPLETELY PRIOR TO INSTALLATION.

MAXTRAC IS NOT RESPONSIBLE FOR ANY DAMAGE OR INJURY DUE TO IMPROPER INSTALLATION OR MAINTENANCE.

Installer is responsible to insure a safe and controllable vehicle after performing modifications. All steps and procedures described in these instructions were performed while the vehicle was properly supported on a two post vehicle lift with safety jacks. Included instructions are recommended guidelines only.

Max Trac Suspension recommends reference to the OE Service Manual corresponding to the model and year of vehicle when either disassembling or assembling factory and related components.

Use caution during all disassembly and assembly steps to insure suspension components are not over extended, causing damage to any vehicle components and parts included in this kit. Unless otherwise specified, tighten all bolts and fasteners to standard torque specifications listed within the OE Service Manual.

Suspension components that use rubber or urethane bushings should be tightened with the vehicle at normal ride height. This will prevent premature wear or failure of the bushing and maintain ride comfort.

Larger tire and wheel combinations may increase leverage on suspension, steering, and related components.

Due to payload options and initial ride height variances, the amount of lift is a base figure. Final ride height dimensions may vary in accordance to original vehicle ride height. Always measure the vehicle ride height prior to beginning of installation.

MAXTRAC SUSPENSION DOES NOT ADVISE USING WHEELS WIDER THAN 9" OR WHEELS WITH LESS THAN 4.5" BACKSPACING. DOING SO WILL RESULT IN VOIDING ANY AND ALL MANUFACTURER WARRANTIES

Max Trac Suspension does not recommend the combined use of suspension lifts, body lifts, or other lifting devices.

Final Checks & Adjustments

Once the vehicle is lowered to the ground, check all parts which have rubber or urethane components to ensure proper torque. Torque lug nuts to the wheel manufacturer specs.

Move vehicle backwards and forwards a short distance to allow suspension components to settle. Turn the front wheels completely left then right and verify adequate tire, wheel, brake line, and ABS wire clearance.

Test and inspect steering, brake and suspension components for tightness and proper operation. Inspect brakes, hoses, and ABS lines for adequate slack at full extension, and adjust as necessary.



ADDITIONAL WARNINGS

WARNING

Max Trac Suspension products should ONLY be installed by a certified professional mechanic with experience working on and installing suspension products. Professional knowledge and skill will typically yield the best installation results.

If you need a list of installers in your area, please contact Max Trac Suspension customer service to find one of our authorized dealers. Max Trac Suspension does not warrant work performed by any dealer, installer, or mechanic.

- All lifted vehicles may require additional driveline modifications and/or balancing.
- A Factory Service Manual for your specific Year/ Make / Model should be referenced during installation.
- Use of a vehicle hoist will greatly reduce installation time.
- Speedometer / computer calibration is required if changing +/- from factory tire diameter.
- Vehicle must be in excellent operating condition. Repair or replace any and all worn or damaged components prior to installation.

FAILURE TO PERFORM POST INSTALLATION INSPECTION AND/OR CHECKS MAY RESULT IN VEHICLE COMPONENT DAMAGE AND/OR PERSONAL INJURY OR DEATH.

RECHECK ALL HARDWARE FOR PROPER TORQUE VALUES AFTER 500 MILES, AND THEN PERIODICALLY AT EACH SERVICE INTERVAL THERAFTER.

Vehicle Handling Warning

Increasing the height of your vehicle raises the center of gravity and **WILL** affect stability and control. Use caution on turns and when steering. Vehicles with larger tires and wheels will handle differently than stock vehicles. Take time to familiarize yourself with the handling of your vehicle after product installation.

Wheel Alignment/Headlamp Adjustment

It is necessary after installation to have a wheel alignment performed by a certified alignment technician. Align the vehicle to factory specifications. It is recommended that your vehicle alignment be checked after any off-road driving. In addition to vehicle alignment, it is necessary to check and adjust vehicle head lamps for proper aim and alignment. If the vehicle is equipped with active or passive safety/collision monitoring and / or avoidance systems including, but not limited to, camera-or radar-based systems, check and adjust your vehicle's systems for proper aim and function.

Braking Warning

Generally, braking performance and capabilities are decreased when significantly larger or heavier tires and wheels are used. Take this into consideration while driving. Also, changing axle gear ratios or using tires that are taller or shorter than factory height will cause an erroneous speedometer reading. On vehicles equipped with an electronic speedometer, the speed signal impacts other important functions as well. Speedometer recalibration for both mechanical and electronic types is highly recommended.



SAFETY WARNINGS

SAFETY WARNING

MISUSE OF THIS PRODUCT COULD LEAD TO INJURY OR DEATH.

- Suspension systems or components that enhance the on and off-road performance of your vehicle may cause it to handle differently than it did from the factory. EXTREME CARE must be used to prevent loss of control or vehicle rollover during operation.
- ALWAYS operate your vehicle at reduced speeds and maintain distance between vehicles and obstacles to ensure your ability to control your vehicle under all driving conditions. Failure to drive safely may result in serious injury or death to the driver and passengers.
- Driver and passengers must ALWAYS wear seat belts, avoid rapid steering angles and rates and other sudden maneuvers.
- You should NEVER operate your vehicle under the influence of alcohol or drugs.
- Please check all factory components for excessive wear and tear. Please replace worn factory parts before installing any suspension kits. Failure to do so will void any Max Trac warranty.
- Please inspect all wheel bearings and hub bearings for excessive wear and replace worn components before installing suspension kits. These hub and wheel bearings may wear out sooner with installation of larger tires and wheels. MaxTrac does not warranty these factory parts at any time, also using any wheel that MaxTrac does not recommend will void any warranty of MaxTrac components.
- Constant maintenance is required to keep your vehicle safe. Thoroughly inspect your vehicle before and after every off-road use.
- It is the responsibility of the retailer and/or the installer to review all state and local laws with the end user of this product related to bumper height laws and the lifting of a vehicle before the purchase and installation of any Max Trac products.
- It is the responsibility of the driver to check the area around the vehicle for obstructions, people, and animals before moving the vehicle.
- All lifted vehicles have increased blind spots. Take note of these prior to operating the vehicle.

DAMAGE, INJURY AND/OR DEATH CAN OCCUR IF ANY OF THE ABOVE WARNINGS ARE NOT FOLLOWED.